

ANC-Ultra-2030 Wall Panel (Ultra Encapsulated, 2", 3.0- lb den.)

All Noise Control Ultra Wall Panels absorb sound waves by adding soft, porous, open-celled materials to any environment. The Ultra Wall panel achieves this with a durable, cleanable, and virtually rip-proof facing. The 2" thick, 3-lb. pcf density fiberglass sound absorption core is totally encapsulated on all sides by a white fiberglass scrim reinforced polypropylene facing. There are a number of mounting options available. These panels have a Class A flammability rating per ASTM E-84.

- Class A Flammability Rated
- Durable, Washable
- Puncture and Stain resistant
- NRC .95

Applications:

Typically used in clean rooms, swimming pools, hospitals, kennels, warehouses, factories, or anywhere that requires panels to be steam cleaned. In addition these panels are commonly specified for use in mechanical rooms, wastewater treatment plants and blower buildings to reduce reverberation and overall noise levels.

Product Data:

Description	Nominal 3.0 lb/ft ³ fiberglass core wrapped in a fiberglass scrim reinforced polypropylene facing. (Color: White)
Nominal thickness	2.0 inches
Fiberglass Density	3 lbs. per cu. ft.
Standard size	4' x 8'
Temperature Range	40° to +265° F

Acoustical Performance:

Sound Absorption Data

Product	OCTAVE BAND FREQUENCIES (Hz)						NRC
	125	250	500	1000	2000	4000	
ANC-UE-2030	.26	.80	1.23	1.00	.71	.43	.95