

ASSEMBLY INSTRUCTIONS: CEILING MOUNTED ENCLOSURE

1. Layout and mark area to be enclosed.
2. Referring to the track layout drawing for connector positions and while the hardware is on the ground, slide the roller track (16 RT) through the connectors. To make sliding the track into the connectors easier, squeeze the ends of the track together as you slide it into the connector. Where two pieces of track meet inside a connector make sure to de-burr the ends of the track and push the butting ends together so that they fit snugly. This prevents the rollers from getting stuck in a “pot hole” inside the connector. **Be sure to see the track orientation detail to ensure that the enclosure is assembled as designed.**

NOTE: A double track system is created by using two pieces of single track held together by a double track connector. If needed cut the supplied 16 RT to length desired.

3. Lift the track and hardware to the desired location and attach all connectors, to ceiling. (Refer to track layout drawing for locations).
4. Install the acoustical curtain panels per the appropriate instructions.
5. After acoustical curtain panels are installed Adjust hardware as necessary to accommodate curtains. Install setscrews through top of track connectors into track
6. Install 16 ES end stops in all open ends of track to prevent rollers from running out of track.
7. Line up existing holes or drill holes as necessary in track to accept setscrews that lock into the track thru the track connectors (use a 3/16 inch hex key).